



- Easy installation and maintenance
- Standard protector overload device
- 10-pocket, oblique lay liftwheel for smooth chain operation, constant chain speed and reduced chain wear
- NEMA 4, industrial-rated control station
- Gear train lifetime lubricated with non-oxidizing grease
- Alloy load chain for smooth operation and maximum chain life
- Thermally-protected hoist duty motor
- Dual brake system - D.C. plus regenerative
- Rugged cast aluminum alloy hoist frame
- Small, compact design for commercial applications
- Totally enclosed, non-ventilated hoist frame protects the motor from environmental contamination
- Optional impact-resistant chain container is available
- Rigid latch style upper hook prevents tangling of power cord
- Precision bearings used throughout the hoist
- Hardened forged steel latch-style lower hook rotates 360°
- True vertical lift
- Lifetime Warranty

Specifications & Dimensions

Capacity	Lift Speed	Motor	Reeving	Hoist Catalog Number				Lift	A	B	C	D	Shipping Weight
				*115-1-60	115-1-60	230-3-60	460-3-60						
lbs.	FPM	H.P.					ft.	in	in	in	in	lbs.	
250	16	1/16	single	931770	-	-	-	10	11-1/16	3-7/8	2-15/16	3	26
	16		single	-	931769	931771	931772						28
	24		single	-	-	931774	931775						28
	40		single	-	-	931777	931778						28
300	16	1/16	single	931781	-	-	-	10	11-1/16	3-7/8	2-15/16	3	26
	16		single	-	931780	931783	931784						28
	24		single	-	-	931786	931787						28
	40		single	-	-	931806	931807						28
500	8	1/16	double	931843	-	-	-	10	12-1/8	5-3/4	2-3/8	3-9/16	32
	8		double	-	931842	931844	931845						34
	12		single	931838	-	-	-						26
	12		single	-	931837	931839	931840						28
	20		double	-	-	931847	931848						34
	24		single	-	-	931862	931863						28
600	8	1/16	double	931791	-	-	-	10	12-1/8	5-3/4	2-3/8	3-9/16	34
	8		double	-	931790	931793	931794						34
	12		double	-	-	931796	931797						34
	20		double	-	-	931880	931881						34
1000	6	1/16	double	931866	-	-	-	10	12-1/8	5-3/4	2-3/8	3-9/16	34
	6		double	-	931865	931867	931868						34
	8		double	-	-	931870	931871						32
	12		double	-	-	931873	931874						32

* Contractor in PB station