

Rigger lever operated hoist



Designed for moderate commercial applications, this lightweight, compact tool stores easily and features:

- Flexible, non-binding CM load chain
- Forged upper and lower hooks with latches standard
- Free-wheeling chain for fast attachment
- Clover leaf chain guides and stripper seat chain in liftwheel reduce chance of jamming
- Unlimited lift by ordering any length chain
- Ratchet, driving pawl and holding pawl for load control
- One lever used to change from lifting to lowering and back to lifting
- Easy maintenance
- One-year warranty
- Metric rated
- Made in U.S.A.

* ⚠ WARNING
Overloading and improper use can result in injury.
To avoid injury: <ul style="list-style-type: none"> • Do not exceed working load limit, load rating capacity • Do not use to lift people or loads over people. • use only alloy chain for overhead lifting. • Read and follow all instructions.

Specifications

Rated capacity* (tons)	Product code	Standard lift† (ft.)	Reeving	Pull to lift full load (lbs.)	Minimum distance between hooks (in.)	Lever length (in.)	Hook throat openings (in.)	Shipping weight (lbs.)
3/4	2301	5	1	98	10 3/4	15 5/8	1 1/32	8 3/4
1 1/2	2302	5	2	98	12 1/2	15 5/8	1 1/32	13 3/4

† Can be supplied with lifts longer than 5 feet