

# TECHNICAL LINE SHAFT HORSEPOWER DATA



## GENERAL

Since many sections and accessories may be coupled to one drive, it is important that the motor be properly sized for each application.

Table I (at right) may be used as a general guide to selection of drive motor sizes for typical installations.

When powered accessories are added to straight sections, the maximum allowable length must be adjusted. Table II (below) lists the horsepower required for the various accessories.

Factors that are important to power requirements include the number of rollers per foot, the total length of straight sections, the number and type of powered accessories and the desired speed of the conveyor.

HORSE-POWER	ROLLER CENTERS	30FPM	45FPM	60FPM	75FPM	90FPM	120FPM
1/3	3"	57	37	28	22	19	14
1/3	4"	75	50	37	30	25	19
1/3	6"	112	75	56	45	37	28
1/2	3"	84	56	42	34	28	20
1/2	4"	112	75	56	45	38	28
1/2	6"	168	112	84	67	56	42
3/4	3"	126	84	63	50	42	32
3/4	4"	168	112	84	67	56	42
3/4	6"	200	168	126	100	84	63
1	3"	-	112	84	67	56	42
1	4"	-	150	112	90	75	56
1	6"	-	200	168	135	112	84
1-1/2	3"	-	-	126	100	84	63
1-1/2	4"	-	-	168	135	112	84
1-1/2	6"	-	-	200	200	168	126
2	3"	-	-	-	135	112	84
2	4"	-	-	-	180	150	112
2	6"	-	-	-	200	200	168

**NOTE:** Drive cannot be located more than 75' from either end on 3" RC; 90' from either end on 4" RC; or 100' from either end on 6" RC.

## 796LS CAPACITY

The drive capacity accepted is 15 lbs. per roller. The type of package and/or material being conveyed may increase or decrease this capacity. Very hard, rigid, flat bottom containers increase roller capacity while soft, uneven surfaces will decrease it.

**NOTE:** Drive capacity for model 738LS is 10 lbs. per roller; 7.5 lbs. roller capacity for model 738LSC.

## ROLLER CENTERS

The number of rollers required per package is dependent upon package weight, package length, drive capacity per roller, and type of surface. The package formulas (at right) should be used to determine the maximum allowable roller centers. Use the lesser of the two values rounded to the nearest standard roller centers. Finally, only use model 738LS for light duty applications where close roller centers are required.

### PACKAGE WEIGHT FORMULA

+ Length of package (in inches)  
 ÷ Weight of package  
 = Subtotal  
 × 15 # (Drive capacity of rollers; use 10 # for 738LS)  
 = Maximum Roller Centers

### PACKAGE LENGTH FORMULA

+ Length of package (in inches)  
 ÷ 3  
 = Maximum Roller Centers

POWERED ACCESORIES	30FPM	45FPM	60FPM	75FPM	90FPM	120FPM
30° CURVE	.03	.05	.06	.07	.09	.12
45° CURVE	.04	.07	.09	.11	.13	.17
60° CURVE	.06	.09	.12	.15	.18	.24
90° CURVE	.08	.12	.15	.19	.23	.30
Converging Spur	.13	.18	.26	.34	.40	.52
Diverging Spur	.16	.23	.32	.39	.46	.63
Powered Gate	.04	.05	.07	.09	.11	.15
Chain Cross Over	.02	.02	.02	.03	.04	.05

**NOTE:** When accessories are added to straight line shaft conveyor sections, the maximum allowable lengths shown in Table I must be adjusted. Use the adjustment formula at right to determine the adjusted maximum length.

### LINE SHAFT ADJUSTMENT FORMULA

Maximum HP (Table I)  
 - Total HP of accessories (Table II)  
 = Subtotal  
 ÷ Maximum HP (Table I)  
 × Max. allowable straight length (Table I)  
 = Adjusted straight Length

