



Panel Mount Alarms 855P

- Visual, audible, or combined indication
- Completely enclosed front, suitable for harsh washdown environments
- Ingress protection rating UL Type 4/4X/13, IP65
- Rear-securing and finger-safe terminals
- Mount in a standard 22.5 mm hole or 30.5 mm hole with adapter

855P panel mount alarms allow local indication of the status of a machine or equipment while enhancing space efficiency with devices ready to be installed in a control panel. These devices include features that preserve the control panel integrity and reduce installation time. Alarm options include sounders, status indicator beacons, xenon strobes, and sounders with status indicator combination, as well as dual-circuit alarms.

Bulletin 855PB LED Beacon

Mounting ring to secure device to the rear of the panel



855P Sounders

Removable plug-in terminal block
Keyed to avoid wiring mistakes



855PC Combined Sounder w/ LED beacon

Completely enclosed front tamper/vandal resistant suitable for wash down environments



Bulletin 855PS Xenon Strobe Beacon

Voltage color coding for easy identification of the circuit



2-Color Half-Lens (with barrier)

Signal up to two different conditions on a machine with only one device



Product Selection

855P Panel Mount Sounders

Voltage	Size [mm]	Cat. No.
12...24V AC/DC	30 (72 dB)	855P-B30SE22
	30 (80 dB)	855P-B30SH22
	45	855P-B30ME22
	65	855P-B30LE22
120V AC	30 (72 dB)	855P-B10SE22
	30 (80 dB)	855P-B10SH22
	45	855P-B10ME22
	65	855P-B10LE22

Accessories

Description	Cat. No.
22.5...30.5 mm hole adapter kit	855P-AHA1

Specifications

Housing Material	Base	Polycarbonate (black)
	Lens	Polycarbonate (red, amber, yellow, green, blue, and clear)
Environmental Ratings	UL Type 4/4X/13, IP65	
Operation Temperature Range	-25...+60 °C (-13...+140 °F)	
Mounting	Central mounting for bore holes 22 mm or 30.5 mm with hole adapter kit (Cat. No. 855P-AHA1)	
Certifications	cULus Listed, CE Marked	



Need Help?

The Rockwell Automation Support Center is your 24/7 support for the answers you need now.

www.rockwellautomation.com/support/overview.page

855PS Panel Mount Strobes and 855PB Selectable Steady or Flashing LED Beacons

Voltage	Diameter [mm]	Lens Color	Panel Mount Strobe	Selectable Steady/Flashing LED Beacon
			Cat. No.	Cat. No.
24V AC/DC	30	Green	855PS-B24SE322	855PB-B24SE322
		Red	855PS-B24SE422	855PB-B24SE422
	45	Green	855PS-B30ME322	855PB-B24ME322
		Red	855PS-B30ME422	855PB-B24ME422
	65	Green	855PS-B30LE322	855PB-B24LE322
		Red	855PS-B30LE422	855PB-B24LE422
120V AC	30	Green	855PS-B10SE322	855PB-B10SE322
		Red	855PS-B10SE422	855PB-B10SE422
	45	Green	855PS-B10ME322	855PB-B10ME322
		Red	855PS-B10ME422	855PB-B10ME422
	65	Green	855PS-B10LE322	855PB-B10LE322
		Red	855PS-B10LE422	855PB-B10LE422

855PC Combined Sounders with LED Beacon and 855PD Dual-Circuit Alarms

Function	Voltage	Diameter [mm]	Color(s)	Combined Sounder with LED Beacon	Dual Circuit Alarm	
				Cat. No.	Cat. No.	
Sounder with LED	24V AC/DC	45	Green	855PC-B24ME322	855PD-B24MEC1322	
			Red	855PC-B24ME422	855PD-B24MEC1422	
		65	Green	855PC-B24LE322	855PD-B24LEC1322	
			Red	855PC-B24LE422	855PD-B24LEC1422	
	120V AC	45	Green	855PC-B10ME322	855PD-B10MEC1322	
			Red	855PC-B10ME422	855PD-B10MEC1422	
Half-lens, steady LED beacon ¹	24V AC/DC	30	Red & Green	-	855PD-B24SEH4322	
		45			855PD-B24MEH4322	
		65			855PD-B24LEH4322	
	120V AC	45	Red & Green	-	855PD-B10MEH4322	
					65	855PD-B10LEH4322
						855PD-B10LEH4322

¹ Full lens style with 2 LED beacons also available