

SPANCO GANTRY CRANES

SELECTOR GUIDE

							
Gantry Crane Type	T-Series	A-Series	Aluminum	E-Series	PF-Series	Single Leg	Wide Flange
Key Features	Adjustable span, height, & tread	Greater clear spans; adjustable height models	Lightweight, fast assembly, & disassembly, adjustable	Economical, durable, & dependable	High capacity, high height, & long span	Maximized floor space	For specialized applications
Standard Capacities*	Up to 10 tons	Up to 10 tons	Up to 3 tons	Up to 5 tons	Up to 15 tons	Up to 15 tons	Up to 15 tons
Max. Height*	24' <i>(OVERALL HEIGHT)</i>	16' <i>(UNDER BEAM)</i>	12' <i>(UNDER BEAM)</i>	14' <i>(UNDER BEAM)</i>	35' <i>(UNDER BEAM)</i>	35' <i>(UNDER BEAM)</i>	35' <i>(UNDER BEAM)</i>
Standard Spans*	Up to 40'	Up to 40'	Up to 20'	Up to 12'	Up to 50'	Up to 50'	Up to 55'
Powered Trolley Compatible	Yes	No	No	No	Yes	Yes	Yes
Power Travel Compatible	No	No	No	No	Yes	Yes	Yes
Key Options*	Cart Kit & Height Adjustment Kit	Steel w/ fixed or adjustable span; Aluminum w/ adjustable span	Pneumatic tires, single or dual	Adjustable height; wheel brakes	Trackless, angle guide, or V-groove track guidance	Single (semi), double leg or wide-flange designs	Single (semi) or double leg designs; double girder option

*The maximum capacities and dimensions listed above vary depending on the combination of the span, capacity, and HUB selected for the system. Larger spans and heights may be available. Contact your local Spanco dealer or call us at 800-869-2080.